





RoHS



- SPECIFICATIONS
 - Voltage rating: 250V AC, DC
 - Current rating: 5A, AC, DC
 - Withstanding Voltage: 1500V AC/minute
 - Insulation resistance: 1000MΩ min
 - Temperature range: -25° C~+85° C
- HOUSING
 - Part No.: H2545NKT-NP
 - Poles : 03, 05, 07, 08, 09, 20P
 - Housing Material: PA66 15%GF UL94V-0 Black
 - The Dimension Marked “▼” Must Be Recorded



Poles	Dimensions (mm)	
	A	B
03	5.08	7.62
05	10.16	12.70
07	15.24	17.78
08	17.78	20.32
09	20.32	22.86
20	48.26	50.80

D	更新图面	2019-06-03	陈雄军							
C	修打版本	2015-11-04	陈雄军							
B	变更图宽格式内容	2013-12-27	陈雄军							
A	新版本	2011-05-24	陈雄军							
H	说明	日期	承认							
1	版次	REV.	APPRO.							
1	1	2	3	4	5	6	7	8	9	10

一般公差	0±0.30
GENERAL TOLERANCE:	.00±0.25
	.000±0.05
ANGLE: ±1°	
绘图/DR	陈雄军
审核/CHECK	陈雄军
核准/APPRO	胡进
日期/DATE	2019-06-03

XYDZ® 东莞市祥运连接器有限公司 Dongguan XiangYun Connectors CO., Ltd	
投影法 Projection	第一角投影法 First Angle Projection
单位 Unit	MM
比例/Scale	1:1
大小/Size	A4
页码/SHEET	1/1
版本/Rev	D
品名 (PART NAME)	Molex 2.54mm Male Housing Connector Series
料号 (PART NO)	H2545NKT-NP
状态码	C