RoHS

H4202N-2xNP-X

None:Pa66-V2 Natural
BK:Pa66-V2 Black
V0:Pa66-V0 Natural
V0BK:Pa66-V0 Black

■ SPECIFICATIONS

- Voltage rating: 600V AC, DC
- Current rating: 7A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance:1000MΩ min
- Temperature range: -25° C~+85° C

■ HOUSING

- Part No.: H4202N-2xNP-X
- Poles: 02-24P
- Housing Material: PA66 UL94V-2 or UL94V-0
- Mates With: H4201 Dual Row Receptacle
- Use With: T4201 Terminals
- The Dimension Marked "▼" Must Be Recorded











CIRCUIT SIZE LAYOUT

PART NO.	Dimensions(mm) A	B
2x01	--	5.60
2x02	4.20	9.80
2x03	8.40	14.00
2x04	12.60	18.20
2x05	16.80	22.40
2x06	21.00	26.60
2x07	25.20	30.80
2x08	29.40	35.00
2x09	33.60	39.20
2x10	37.80	43.40
2x11	42.00	47.60
2x12	46.20	51.80

版次 REV.	说明 DESCRIPTION	日期 DATE.	承认 APPRO.
D	更新图面	2019-07-03	PH.Duan
C	修订版本	2015-11-04	陈雄军
B	变更图宽格式内容	2013-12-27	陈雄军
A	新版本	2011-05-24	陈雄军

一般公差 GENERAL TOLERANCE:	0±0.30 .0±0.25 .00±0.20 .000±0.05 ANGLE. ±1°		
绘图/DR	PH.Duan		
审核/CHECK	陈雄军		
核准/APPRO	胡 进		
日期/DATE	2019-07-03		

XYDZ® 东莞市祥运连接器有限公司
Connectors DongGuan XiangYun Connectors CO.,Ltd

投影法 Projection		品 名 (PART NEME)	Molex 4.20mm 无翅膀 Female Housing Connector Series
单位 Unit	MM		
比例/Scale	1:1		
大小/SIZE	A4		
页码/SHEET	1/1	料 号 (PART NO)	H4202N-2xNP-X
版本/Rev	D		状态码 C