RoHS



■ SPECIFICATIONS

- Voltage rating: 300V AC, DC
- Current rating: 10A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance:1000MΩ min
- Temperature range: -25° C~+85° C

■ HOUSING

- Part No.: H4503F-02P
- Poles: 02P
- Housing Material: PA66 UL94V-0
- Qty:500Pcs/bag
- The Dimension Marked "▼" Must Be Recorded

REV.	DESCRIPTION	DATE.	APPRO.
B	更新图面	2019-06-03	PH.Duan
A	新版本	2018-03-21	Jeff

一般公差 GENERAL TOLERANCE:	0±0.30 .0±0.25 .00±0.20 .000±0.05 ANGLE. ±1°
绘图/DR	PH.Duan
审核/CHECK	陈雄军
核准/APPRO	胡 进
日期/DATE	2019-06-03

XYDZ® 东莞市祥运连接器有限公司
Connectors DongGuan XiangYun Connectors CO.,Ltd

投影法 Projection	
单位 Unit	MM
比例/Scale	1:1
大小/SIZE	A4
页码/SHEET	1/1
版本/Rev	B

品 名 (PART NEME)	YL4.50mm Female Housing Connector Series	
料 号 (PART NO)	H4503F-02P	状态码 C