RoHS





■SPECIFICATIONS

- Voltage rating: 250V AC, DC
- Current rating: 10A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance:1000MΩ min
- Temperature range: -25° C~+85° C
- Contact resistance: 20mΩ max

■WAFER

- Part No.: W5082RT-04P-9TBK
- Housing Material: PA9T UL94V-0 BLACK
- Pin Material: Brass
- Contact Area Plating: Tin-Plated
- The Dimension Marked "▼" Must Be Recorded







P.C.B LAYOUT

REV.	DESCRIPTION	DATE.	APPRO.
B	更新图面	2019-06-03	PH.Duan
A	新版本	2019-03-06	PH.Duan

一般公差 GENERAL TOLERANCE:	0±0.30 .0±0.25 .00±0.20 .000±0.05 ANGLE. ±1°
绘图/DR	PH.Duan
审核/CHECK	陈雄军
核准/APPRO	胡 进
日期/DATE	2019-06-03

XYDZ® 东莞市祥运连接器有限公司
Connectors DongGuan XiangYun Connectors CO.,Ltd

投影法 Projection	
单位 Unit	MM
比例/Scale	1:1
大小/SIZE	A4
页码/SHEET	1/1
版本/Rev	B

品 名 (PART NEME)	Molex 5.08mm 90° 带弹片 Wafer Connector Series	
料 号 (PART NO)	W5082RT-04P-9TBK	状态码 C